



SIZE	KT-1782	KT-1982
Brightness	FULL WHITE 30F/L	FULL WHITE 30F/L
DOT PITCH	0.28 mm	0.26 mm
Resolution	640x480 (VGA)	640x480 (VGA)
	800x600 (SVGA)	800x600 (SVGA)
	1024x768 (XGA)	1024x768 (XGA)
	1280x1024 (UXGA)	1280x1024 (UXGA)
Power Supply	Free Voltage 90~264V	Free Voltage 90~264V
Video signal	Analog 0.7V~1Vp.p	Analog 0.7V~1Vp.p
H.Frequency	30~82KHz	30~82KHz
V.Frequency	50~160Hz	50~160Hz
Control Type	OSD Control	OSD Control
User Control	HV-Size/Pos & H,V-Size., Pincushion, Trapezoid, Degauss, Contrast, Brightness, Pin- Balance, Parallelogram Rotation, Top/Bot-Corner, H,V-Moire, Color temp, Recall, Zoom, Multi- Language	HV-Size/Pos & H,V-Size., Pincushion, Trapezoid, Degauss, Contrast, Brightness, Pin-Balance, Parallelogram Rotation, Top/Bot- Corner, H,V-Moire, Color temp, Recall, Zoom, Multi-Language
Operating Temperature	5~60 degree	5~60 degree
SAFETY	UL,CB,DHHS,CE	CB,CE,TUV,UL,DHHS

Call AESI for additional details: (866) 736-AESI (2374)